

SAX-8206-P

1 or 2 Lines
Cordless Handset
Phone

SAX-8106-P



- 1 or 2 lines cordless handset phone.
- Magnetic hook switch.
- Message waiting indicator.
- 6 customizable service dials.
- Faceplate with customizable hotel logo.
- Coiled cord with bungee cord (anti-drop string).

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

| | Keys | 8206 | 8106 |
|-------------------|--|---|---|
| | | <ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys Hold, Mute, Volume, 6 Service dial keys | <ul style="list-style-type: none"> (0~9, *, #) Line, END Hold, Mute, Volume, 6 Service dial keys |
| Phone Features | <ul style="list-style-type: none"> One or Two Lines Call Hold and resume Handset and ringer volume control | | <ul style="list-style-type: none"> 6 programmable service dials Mute and resume Red color message waiting indicator for ringing and message waiting |
| Display Contents | <ul style="list-style-type: none"> Main logo Service dial icon | | <ul style="list-style-type: none"> Line status Firmware Version |
| Tones | <ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone | | |
| Wireless Standard | <ul style="list-style-type: none"> DECT / CAT iq 2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels | | <ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm |

2. Hardware Specifications

| | |
|-----------------|--|
| Display | <ul style="list-style-type: none"> 1.8" TFT color display |
| LED Indications | <ul style="list-style-type: none"> Message waiting indicator |
| Power | <ul style="list-style-type: none"> PoE : IEEE 802.3af |
| Jacks | <ul style="list-style-type: none"> RJ45 10/100Mbps: LAN port x 1 |
| Ethernet cable | <ul style="list-style-type: none"> 0.5feet x 1 |
| Size and Weight | <ul style="list-style-type: none"> Dimensions:200mm(L) x82mm(W) x 46mm(H), Weight: 455g |

3. Regulatory

| | USA | EU |
|-------------|---|--|
| RF | FCC Part 15D | EN 301406 |
| EMI | FCC Part 15B | EN300386 |
| SAR | | EN62479 |
| Safety | | EN 60950-1 |
| EMC | | EN301489-1/-6 |
| RoHS | <ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) | |
| Temperature | <ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C | <ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C |

Model:

SAX-8106-P

SAX-8206-P

SAX-8106-PBC

SAX-8206-PBC

